Newtop Chemical Materials (Shanghai) Co.,Ltd.

Technical Indicators

FASCAT4202 catalyst dibutyltin dilaurate Arkema PMC

Overview:

Chinese name: FASCAT4202 Catalyst

Alias: Catalyst FASCAT4202, dibutyltin dilaurate, dibutyltin dilaurate, dibutyltin

dilaurate, dibutyltin dilaurate, dibutyltin dilaurate, dibutyltin (1-oxododecanoxy) tin,

di-n-butyltin dilaurate, di-butyltin dilaurate, di-butyltin (1-oxododecanoxy) tin,

di-butyltin dilaurate, di-butyltin (di-butyltin (dodecanoy), di-butyltin dibutyltin

dilaurate, di-butyltin (di-butyltin (dodecanoate), di-butyltin, dibutyltin, dibutyltin,

dibutyltin, dibutyltin, dibutyltin, Dibutyltin dilaurate /T12, di-n-butyltin dilaurate

Physicochemical properties:

CAS 77-58-7

EC 201-039-8

Molecular formula C32H64O4SN

Melting point: 22-24°C

Water solubility: Flash point: 226°C

Property description: Soluble light yellow or colorless oil liquid, low temperature into

white crystals, soluble in benzene, toluene, ethanol, acetone and other organic

solvents, insoluble in water. Specific gravity d (20°C) 1.04-1.06 refraction n (25°C)

1.460-1.470 melting point 22-24°C Quality standard: Tin content Sn18.5±0.5 Volatile


content ≤0.5 chroma (Pt-Co) ≤200#

Newtop Chemical Materials (Shanghai) Co.,Ltd. Technical Indicators



Application:

Used in organic synthesis, as a stabilizer of polyvinyl chloride resin



Leak treatment

Stop leaks as much as possible while ensuring safety. If a minor leak is found, treat it with sand or other absorbent material and place it in a clean, dry container for subsequent treatment. If a large amount of leakage occurs, the leaked material should be collected for subsequent treatment. Avoid material entering groundwater or surface water, because it is not easily degraded by biological matter. All collected leakage materials should be disposed of in accordance with the relevant regulations of the local environmental protection department.

Newtop Chemical Materials (Shanghai) Co.,Ltd.

Technical Indicators

Disclaimer

The information and technical advice provided above are obtained from reliable

sources, but we do not make any commitment to the data provided by us without

express or implied warranties. If you need to use our products, we recommend a series

of tests. The application, use, processing or production of products based on the

technical information provided by us is outside our control and therefore the

responsibility lies with the user. Conditions and methods of handling, storage, use or

disposal of this product are beyond our control and may be beyond our knowledge,

and under no circumstances will we be liable for loss, damage or related expenses

arising from improper handling, storage, use or disposal of this chemical. For more

information, please review the technical safety specifications of our products or

contact our Marketing Services department.

Safety Information:

Catalyst, rinse with soapy water promptly after contact with skin. The staff can wear an

eye mask or safety glasses to achieve the purpose of eye protection. Eye washing and

bathing facilities should be available near the workplace. When working in places that

may come into contact with the product, you should pay attention to personal hygiene

and use detergent to wash the skin in contact with the product before eating, smoking

and leaving the work.

Newtop Chemical Materials (Shanghai) Co.,Ltd.

Technical Indicators

Shelf life:

Remain unopened for two years

Storage and Transportation:

Should be sealed, stored in a dry cool ventilated warehouse

Packing:

200KG/ barrel storage: It is recommended to store in a dry and cool area with proper

ventilation. After the original packaging, please fasten the packaging cover as soon as

possible to prevent moisture and other substances from mixing and affecting the

product performance. Do not inhale dust and avoid contact between skin and mucous

membrane. Smoking, eating and drinking are prohibited in the workplace. Shower and

change after work. Store contaminated clothes separately and use them after washing.

Practice good hygiene.

Technical support and business contacts E-mail: info@newtopchem.com